



Main

Product or component type	Earth leakage protection
Poles description	4P
Neutral position	Left
[In] rated current	63 A
Network type	AC
Earth-leakage sensitivity	30 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Class AC
Rated breaking and making capacity	Im 1500 A conforming to IEC 61008
Rated conditional short-circuit current	I _{nc} 63 A
Utilisation category	AC-23A conforming to IEC 60947-3

Complementary

Device location in system	Outgoer
Network frequency	50/60 Hz
[U _e] rated operational voltage	230/400 V
[U _i] rated insulation voltage	440 V conforming to IEC 60947-3
[U _{imp}] rated impulse withstand voltage	6 kV conforming to IEC 60947-3
9 mm pitches	8
Product weight	0.45 kg
Colour	Grey
Mechanical durability	20000 cycles
Provision for padlocking	Padlockable
Connections - terminals	Tunnel type terminals 35 mm ² flexible Tunnel type terminals 50 mm ² rigid

Environment

standards	IEC 60947-1 IEC 60947-3 IEC 61008
tropicalisation	2
relative humidity	95 % (55 °C)
ambient air temperature for operation	-5...40 °C
ambient air temperature for storage	-40...60 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.