

RCCB, 2-pole, type AC, In: 40 A, 30 mA, Un AC: 230 V



Figure similar

Model		
product brandname		SENTRON
Product designation		RCCB
Design of the product		Instantaneous
General technical data		
Number of poles		2
Size of installation devices / acc. to DIN 43880		1
Protection against electrical shock		Finger and back-of-hand safe
Short-circuit current rating	kA	10
circuit-breaker / Design		5SM3
Mechanical service life (switching cycles) / typical		10 000
Overvoltage category		III
Supply voltage		
Supply voltage		
• at AC / rated value	V	230
• for testing equipment / minimum	V	100

Protection class		
Protection class IP		IP20, if the distribution board is installed, with connected conductors

Switching capacity		
Switching capacity current		
• acc. to EN 60898 / rated value	kA	0.5

Dissipation		
Power loss [W]		
• for rated value of the current / at AC / in hot operating state / per pole	W	4.3
• maximum	W	8.6

Electricity		
Tripping residual current / rated value	mA	30
rated current I_n / IEC, DIN/VDE / at 40 Cel	A	40
Type of fault current		AC
Current / at AC / rated value	A	40
I²t-value / permissible	A ² ·s	70 000
Operating frequency		50Hz

Product details		
Product feature / silicon-free		Yes
Product extension / can be installed / supplementary devices		Yes

Number		
Number of test cycles / for environmental testing / acc. to IEC 60068-2-30		28

Connections		
Connectable conductor cross-section / stranded		
• minimum	mm ²	1
• maximum	mm ²	16
Connectable conductor cross-section / solid		
• minimum	mm ²	1
• maximum	mm ²	16
Tightening torque / with screw-type terminals		
• minimum	N·m	2.5
• maximum	N·m	3
Position / of power supply cord		top or bottom

Mechanical Design		
Height	mm	90
Width	mm	36
Depth	mm	70

Mounting position		any
Installation depth	mm	70
Number of width units		2
Mounting type		DIN rail (REG)
Net weight	g	233

Environmental conditions

Ambient temperature		
• minimum	°C	-5
• maximum	°C	45
• during storage / minimum permissible	°C	-40
• during storage / maximum permissible	°C	75

Certificates

Equipment marking		
• acc. to DIN EN 61346-2		F
• acc. to DIN EN 81346-2		F

General Product Approval	Declaration of Conformity	Test Certificates
---------------------------------	----------------------------------	--------------------------



[sonstig](#)



EG-Konf.

[sonstig](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/5SM3314-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SM3314-0/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=5SM3314-0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://ausschreibungstexte.siemens.com/tiplv>