



PLUG-IN RELAY, 4 CO CONTACTS, 24V DC, 6A, WIDTH 22.5MM

General technical details:		
<b>type of voltage</b>		DC
<b>Control supply voltage</b>		
• for DC / rated value		
• minimum	V	24
• maximum	V	24
<b>Number of NC contacts</b>		
• for auxiliary contacts		0
<b>Number of NO contacts</b>		
• for auxiliary contacts		0
<b>Number of changeover contacts</b>		
• for auxiliary contacts		4
<b>Operating current / of the auxiliary contacts</b>		
• at DC-13		
• at 24 V	A	6
• at AC-15		
• at 230 V	A	4
<b>Design of the switching function</b>		
• guided		changeover switch
		No
<b>Switching behaviour</b>		monostable

### Mechanical design:

Design of the electrical connection		screw-type terminals
Design of the relay operating mechanism		poled
Product component / jumper socket		No
Width	mm	22.5
Height	mm	28
Depth	mm	35

### Certificates/approvals:

#### General Product Approval

#### other



GOST



UR



VDE

[Declaration of Conformity](#)

### Further information:

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

#### Industry Mall (Online ordering system)

<http://www.siemens.com/industrial-controls/mall>

#### CAX-Online-Generator

<http://www.siemens.com/cax>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/LZX:PT570024/all>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=LZX:PT570024](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=LZX:PT570024)

last change:

Jul 1, 2013