



Main

Range of product	Terminal blocks
Product or component type	Terminal block
Technology type	Screw technology
Terminal block type	Removable carrier disconnect
Product specific application	For diode, resistor or cylindrical fuse
Fixing mode	Clip-on mounting on 35 mm asymmetrical DIN rail Clip-on mounting on 35 mm notched symmetrical rail Clip-on mounting on 35 mm symmetrical DIN rail
Nominal cross section	4 mm ²
Length	48 mm
Colour	Grey
Number of points	2
Sale per indivisible quantity	100

Complementary

Width	6 mm
Height	73 mm on 35 mm asymmetrical rail 76 mm on 35 mm notched symmetrical rail 68.5 mm on 35 mm symmetrical DIN rail
Cable cross section	0.5...4 mm ² , flexible without cable end 0.5...6 mm ² , solid 0.5...2.5 mm ² , flexible
[Ue] rated operational voltage	300 V, AWG 22...AWG 10 UL 250 V, AWG 22...AWG 10 CSA 500 V AC/DC conforming to UTE category C 750 V AC conforming to VDE group C 800 V conforming to EN/IEC 60947-7-1 900 V DC conforming to VDE group C
[In] rated current	10 A conforming to VDE group C 3...6.3 A conforming to EN/IEC 60947-7-1 10 A, AWG 22...AWG 10 UL 6.3 A, AWG 22...AWG 10 CSA
Product weight	9 g
Compatibility code	Terminal block

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Environment

Dielectric test voltage	8 kV conforming to EN/IEC 60947-7-1
Product certifications	ASEV CSA UL

Contractual warranty

Warranty period	18 months
-----------------	-----------

Product life status	END OF COMMERCIALISATION
---------------------	--------------------------